



MODEL : PY-  
 NET OPENING :  
 UNITS REQUIRED :  
 PYRAMID COLOR :  
 FINISH :

**SECTION VIEW - PYRAMID SKYLIGHT (PY)**

SCALE : 1/2" = 1"

**SPECIFICATIONS:**

UNIT SHALL BE CONSTRUCTED OF 6063-T5 ALUMINUM EXTRUSION HAVING MINIMUM WALL THICKNESS OF .063. UNIT SHALL BE NEATLY FORMED AND FABRICATED WITH ALL JOINTS AND SEAMS COMPLETELY WELDED BY HELI-ARC PROCESS TO ENSURE MAXIMUM STRENGTH AND WATER TIGHTNESS. ACRYLIC PLASTIC DOME SHALL BE OF A THICKNESS AND CONFIGURATION TO CONFORM WITH U.B.C. REQUIREMENTS AND AAMA SPECIFICATIONS. UNIT SHALL BE SUPPLIED TO JOB READY FOR INSTALLATION.

CALIFORNIA STATE FIRE MARSHAL APPROVAL NO. 4350-054  
 SEE I.C.B.O. ES APPROVAL NO. 1998  
 CITY OF LOS ANGELES RESEARCH REPORT NO. RR-2708

<i>Lane-Aire</i> MANUFACTURING CORP. 2820 El Presidio Street, Carson, California 90749 (323) 636-2324 - FAX (310) 604-3395	
JOB	SHEET OF
ARCH.	
CONTR.	DWG. NO. PY SQR.
SUB. CONTR.	
DRAWN BY -	DATE: